

**Siemens
EcoTech**



SIMATIC S7-1500 Analog input module, AI 8xU/I/R/RTD BA, 16 bit resolution, Accuracy 0.5%, 8 channels in groups of 8; Common mode voltage 4 V DC, Diagnostics; Hardware interrupts; Delivery including infeed element, shield bracket and shield terminal; Front connector (screw terminals or push-in) to be ordered separately

General information	
Product type designation	AI 8xU/I/R/RTD BA
HW functional status	FS01
Firmware version	V1.0.0
• FW update possible	Yes
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
• Prioritized startup	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V15.1 / V16
• STEP 7 configurable/integrated from version	V5.5 SP3 / -
• PROFIBUS from GSD version/GSD revision	V1.0 / V5.1
• PROFINET from GSD version/GSD revision	V2.3 / -
Operating mode	
• Oversampling	No
• MSI	Yes
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	No
Power	
Power consumption from the backplane bus	0.85 W
Power loss	
Power loss, typ.	0.9 W
Analog inputs	
Number of analog inputs	8
• For current measurement	8
• For voltage measurement	8
• For resistance/resistance thermometer measurement	8
permissible input voltage for voltage input (destruction limit), max.	12 V; 12 V continuous, 30 V for max. 1 s
permissible input current for current input (destruction limit), max.	40 mA
Constant measurement current for resistance-type transmitter, typ.	230 ... 370 µA
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
Input ranges (rated values), voltages	
• 0 to +5 V	No

- 0 to +10 V
- 1 V to 5 V
 - Input resistance (1 V to 5 V)
- -1 V to +1 V
 - Input resistance (-1 V to +1 V)
- -10 V to +10 V
 - Input resistance (-10 V to +10 V)
- -2.5 V to +2.5 V
- -25 mV to +25 mV
- -250 mV to +250 mV
- -5 V to +5 V
 - Input resistance (-5 V to +5 V)
- -50 mV to +50 mV
 - Input resistance (-50 mV to +50 mV)
- -500 mV to +500 mV
 - Input resistance (-500 mV to +500 mV)
- -80 mV to +80 mV

No
Yes
10 MΩ
Yes
10 MΩ
Yes
10 MΩ
No
No
No
Yes
10 MΩ
Yes
10 MΩ
Yes
10 MΩ
No

Input ranges (rated values), currents

- 0 to 20 mA
 - Input resistance (0 to 20 mA)
- -20 mA to +20 mA
 - Input resistance (-20 mA to +20 mA)
- 4 mA to 20 mA
 - Input resistance (4 mA to 20 mA)

Yes
25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC
Yes
25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC
Yes
25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC

Input ranges (rated values), thermocouples

- Type B
- Type C
- Type E
- Type J
- Type K
- Type L
- Type N
- Type R
- Type S
- Type T
- Type U
- Type TXK/TXK(L) to GOST

No
No
No
No
No
No
No
No
No
No
No
No

Input ranges (rated values), resistance thermometer

- Cu 10
- Cu 10 according to GOST
- Cu 50
- Cu 50 according to GOST
- Cu 100
- Cu 100 according to GOST
- Ni 10
- Ni 10 according to GOST
- Ni 100
 - Input resistance (Ni 100)
- Ni 100 according to GOST
- Ni 1000
 - Input resistance (Ni 1000)
- Ni 1000 according to GOST
- LG-Ni 1000
 - Input resistance (LG-Ni 1000)
- Ni 120
- Ni 120 according to GOST
- Ni 200
- Ni 200 according to GOST
- Ni 500
- Ni 500 according to GOST
- Pt 10

No
No
No
No
No
No
No
No
No
Yes; Standard/climate
10 MΩ
No
Yes; Standard/climate
10 MΩ
No
Yes; Standard/climate
10 MΩ
No
No
No
No
No
No
No

• Pt 10 according to GOST • Pt 50 • Pt 50 according to GOST • Pt 100 — Input resistance (Pt 100) • Pt 100 according to GOST • Pt 1000 — Input resistance (Pt 1000) • Pt 1000 according to GOST • Pt 200 • Pt 200 according to GOST • Pt 500 • Pt 500 according to GOST	No No No Yes; Standard/climate 10 MΩ No Yes; Standard/climate 10 MΩ No No No No No No
Input ranges (rated values), resistors	
• 0 to 150 ohms • 0 to 300 ohms • 0 to 600 ohms — Input resistance (0 to 600 ohms) • 0 to 3000 ohms • 0 to 6000 ohms — Input resistance (0 to 6000 ohms) • PTC — Input resistance (PTC)	No No Yes 10 MΩ No Yes 10 MΩ Yes 10 MΩ
Cable length	
• shielded, max.	200 m; 50 m at 50 mV
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max. • Integration time, parameterizable • Integration time (ms) • Basic conversion time, including integration time (ms) — additional conversion time for wire-break monitoring — additional conversion time for resistance measurement • Interference voltage suppression for interference frequency f1 in Hz	16 bit Yes 2,5 / 16,67 / 20 / 100 ms 10 / 24 / 27 / 107 ms 4 ms (to be considered in R/RTD/U 1 to 5 V measurement) 8 ms 400 / 60 / 50 / 10 Hz
Smoothing of measured values	
• parameterizable • Step: None • Step: low • Step: Medium • Step: High	Yes Yes Yes Yes Yes
Encoder	
Connection of signal encoders	
• for voltage measurement • for current measurement as 2-wire transducer • for current measurement as 4-wire transducer • for resistance measurement with two-wire connection • for resistance measurement with three-wire connection	Yes Yes; with external supply Yes Yes; Only for PTC Yes; All measuring ranges except PTC; internal compensation of the cable resistances
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.1 %
Temperature error (relative to input range), (+/-)	0.006 %/K
Crosstalk between the inputs, max.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.1 %
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-) • Current, relative to input range, (+/-) • Resistance, relative to input range, (+/-) • Resistance thermometer, relative to input range, (+/-)	0.5 % 0.5 % 0.5 % Ptxxx Standard: ±1.2 K, Ptxxx Climate: ±0.8 K, Nixxx Standard: ±0.8 K, Nixxx

	Climate: ± 0.8 K
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.3 %
• Current, relative to input range, (+/-)	0.3 %
• Resistance, relative to input range, (+/-)	0.3 %
• Resistance thermometer, relative to input range, (+/-)	Ptxxx Standard: ± 1.0 K, Ptxxx Climate: ± 0.5 K, Nixxx Standard: ± 0.5 K, Nixxx Climate: ± 0.5 K
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency	
• Series mode interference (peak value of interference < rated value of input range), min.	40 dB
• Common mode voltage, max.	4 V
• Common mode interference, min.	60 dB
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
• Limit value alarm	Yes; two upper and two lower limit values in each case
Diagnoses	
• Monitoring the supply voltage	No
• Wire-break	Yes; Only for 1 ... 5 V, 4 ... 20 mA, R, and RTD
• Short-circuit	No
• Group error	No
• Overflow/underflow	Yes
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	No
• Monitoring of the supply voltage (PWR-LED)	No
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• for module diagnostics	Yes; red LED
Potential separation	
Potential separation channels	
• between the channels	No
• between the channels, in groups of	8
• between the channels and backplane bus	Yes
Permissible potential difference	
between the inputs (UCM)	8 V DC
Between the inputs and MANA (UCM)	4 V DC
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Siemens Eco Profile (SEP)	Siemens EcoTech
Ecological footprint	
• environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	38.6 kg
— global warming potential, (during production) [CO2 eq]	14.4 kg
— global warming potential, (during operation) [CO2 eq]	24.6 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.44 kg
product functions / security / header	
signed firmware update	No
data integrity	No
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-30 °C; From FS05
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C; From FS05
• vertical installation, max.	40 °C

Altitude during operation relating to sea level					
● Installation altitude above sea level, max.		5 000 m; Restrictions for installation altitudes > 2 000 m, see manual			
Dimensions					
Width	35 mm				
Height	147 mm				
Depth	129 mm				
Weights					
Weight, approx.	250 g				
Classifications					
		Version	Classification		
	eClass	14	27-24-22-01		
	eClass	12	27-24-22-01		
	eClass	9.1	27-24-22-01		
	eClass	9	27-24-22-01		
	eClass	8	27-24-22-01		
	eClass	7.1	27-24-22-01		
	eClass	6	27-24-22-01		
	ETIM	9	EC001420		
	ETIM	8	EC001420		
	ETIM	7	EC001420		
	IDEA	4	3562		
	UNSPSC	15	32-15-17-05		
Approvals / Certificates					
General Product Approval					
					
General Product Approval				EMV	Test Certificates
Miscellaneous	KC		Miscellaneous		Special Test Certificate
Test Certificates	Maritime application				
Miscellaneous					
other	Railway		Environment		
Confirmation	Confirmation	Special Test Certificate		Environmental Confirmations	Environmental Confirmations