

SIMATIC WinAC RTX F 2010, Single License for 1 install., R-SW, SW and documentation on DVD, License key on USB stick, Class A, 2 languages (de, en), executable on WinXP SP2, SP3 or Windows 7 32 bit, incl. InterValzero RTX, Reference HW: SIMATIC PC



General information	
Product type designation	RTX F 2010
Firmware version	V4.6
Product function	
• Isochronous mode	Yes
Engineering with	
• Programming package	STEP 7 V5.5 or higher + S7 Distributed Safety V5.4 SP5 or higher + S7 F Configuration Pack V5.5 SP6 HF1 / iMap V3.0 SP1; STEP 7 in TIA Portal V13 or higher + STEP 7 Safety Advanced V13
Memory	
Type of memory	RAM
Work memory	
• integrated (for program)	4 Mbyte; Adjustable; depends on Non Paged Memory Pool
• integrated (for data)	4 Mbyte; Adjustable; depends on Non Paged Memory Pool
Load memory	
• integrated RAM, max.	Adjustable; depends on Non Paged Memory Pool
CPU processing times	
for bit operations, typ.	0.004 $\mu$ s
for fixed point arithmetic, typ.	0.003 $\mu$ s
for floating point arithmetic, typ.	0.004 $\mu$ s
Reference platform	Pentium 4, 2.4 GHz
CPU-blocks	
DB	
• Number, max.	65 535; Limited only by RAM set for data
• Size, max.	64 kbyte
FB	
• Number, max.	65 536; Limited only by RAM set for code
• Size, max.	64 kbyte
FC	
• Number, max.	65 536; Limited only by RAM set for code
• Size, max.	64 kbyte
OB	
• Number, max.	Limited only by RAM set for code
• Size, max.	64 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	1; OB 10
• Number of delay alarm OBs	1; OB 20
• Number of cyclic interrupt OBs	9; OB 30-38
• Number of process alarm OBs	1; OB 40
• Number of ODK OBs	3; OB 52-54

<ul style="list-style-type: none"> <li>• Number of DPV1 alarm OBs</li> <li>• Number of isochronous mode OBs</li> <li>• Number of startup OBs</li> <li>• Number of asynchronous error OBs</li> <li>• Number of synchronous error OBs</li> </ul>	3; OB 55-57 2; OB 61-62 2; OB 100, 102 7; OB 80, 82-85, 86, 88 2; OB 121, 122
<b>Nesting depth</b>	
<ul style="list-style-type: none"> <li>• per priority class</li> <li>• additional within an error OB</li> </ul>	24 24
<b>Counters, timers and their retentivity</b>	
<b>S7 counter</b>	
<ul style="list-style-type: none"> <li>• Number</li> </ul>	2 048
<b>Retentivity</b>	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	8
<b>Counting range</b>	
— adjustable	Yes
— lower limit	0
— upper limit	999
<b>IEC counter</b>	
<ul style="list-style-type: none"> <li>• present</li> <li>• Type</li> <li>• Number</li> </ul>	Yes SFB Unlimited (limited only by RAM capacity)
<b>S7 times</b>	
<ul style="list-style-type: none"> <li>• Number</li> </ul>	2 048
<b>Retentivity</b>	
— adjustable	Yes
— lower limit	0
— upper limit	2 047
— preset	0
<b>Time range</b>	
— lower limit	10 ms
— upper limit	9 990 s
<b>IEC timer</b>	
<ul style="list-style-type: none"> <li>• present</li> <li>• Type</li> <li>• Number</li> </ul>	Yes SFB Unlimited (limited only by RAM capacity)
<b>Data areas and their retentivity</b>	
Retentivity without UPS and PS Extension Board	128 kbyte with SIMATIC IPC427C and HMI IPC477C; further SIMATIC PCs on request
Retentivity with UPS	all data
<b>Flag</b>	
<ul style="list-style-type: none"> <li>• of which retentive</li> <li>• Retentivity preset</li> <li>• Number of clock memories</li> </ul>	MB 0 to MB 16383 MB 0 to MB 15 8
<b>Data blocks</b>	
<ul style="list-style-type: none"> <li>• Retentivity adjustable</li> <li>• Retentivity preset</li> </ul>	Yes; via non-retain property on DB Yes
<b>Local data</b>	
<ul style="list-style-type: none"> <li>• adjustable, max.</li> <li>• preset</li> <li>• per priority class, max.</li> </ul>	64 kbyte 32 kbyte 61 440 byte
<b>Address area</b>	
<b>I/O address area</b>	
<ul style="list-style-type: none"> <li>• Inputs</li> <li>• Outputs</li> </ul>	16 kbyte 16 kbyte
<b>Subprocess images</b>	
<ul style="list-style-type: none"> <li>• Number of subprocess images, max.</li> </ul>	15
<b>Digital channels</b>	

• Inputs	128 000
• Outputs	128 000
<b>Analog channels</b>	
• Inputs	8 000
• Outputs	8 000
<b>Hardware configuration</b>	
Number of operable FMs and CPs (recommended)	
• FM	4; FM distributed: FM 350-1, FM 350-2, FM 351, FM 352 / FM 352-5, FM 353, FM 354, FM 355, FM 355-2
• CP, PtP	2; CP 340, CP 341 distributed
• CP, LAN	Over PC CP
<b>Submodules</b>	
• Number of submodules, max	4
— of which PROFIBUS, max.	4; Supported interfaces: see 1st and 2nd interface
— of which Industrial Ethernet, max.	1; Supported interfaces: see 3rd and 4th interface
<b>Time of day</b>	
Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
Operating hours counter	
• Number	8
Clock synchronization	
• supported	Yes
• to PC-CP, slave	Yes
• on Ethernet via NTP	Yes
<b>1. Interface</b>	
Interface type	CP 5611-A2, CP 5621, integrated PROFIBUS interface of the SIMATIC PC
Isolated	Yes
Number of simultaneously operable CPs, max.	1
<b>Protocols</b>	
• MPI	No
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	No
<b>PROFIBUS DP master</b>	
• Number of connections, max.	8
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	64
<b>Services</b>	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Equidistance	Yes; Only in conjunction with isochronous mode
— Isochronous mode	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
— DPV0	Yes
— DPV1	Yes
<b>Address area</b>	
— Inputs, max.	16 kbyte
— Outputs, max.	16 kbyte
<b>User data per DP slave</b>	
— Inputs, max.	244 byte
— Outputs, max.	244 byte

## 2. Interface

Interface type	CP 5613, CP 5613-A2, CP 5603, CP 5623
Isolated	Yes
Number of simultaneously operable CPs, max.	4
<b>Protocols</b>	
• MPI	No
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	No
<b>PROFIBUS DP master</b>	
• Number of connections, max.	50
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	125
<b>Services</b>	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Equidistance	Yes; Only in conjunction with isochronous mode
— Isochronous mode	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
— DPV0	Yes
— DPV1	Yes
<b>Address area</b>	
— Inputs, max.	16 kbyte
— Outputs, max.	16 kbyte
<b>User data per DP slave</b>	
— Inputs, max.	244 byte
— Outputs, max.	244 byte

## 3. Interface

Interface type	PROFINET
Isolated	Yes
Number of simultaneously operable CPs, max.	1; Intel Pro/1000 (Intel 82571EB, 82573L, 82574L, 82541PI; non-shared IRQ required); integrated IE interface SIMATIC PC 4x7B, 6x7B, 8x7B, IPC4x7C, IPC6x7C, IPC8x7C
automatic detection of transmission rate	Yes; 10/100 Mbit/s
Autonegotiation	Yes
Autocrossing	Yes
<b>Interface types</b>	
• Number of ports	1
• integrated switch	No
<b>Protocols</b>	
• PROFINET IO Controller	Yes
• PROFINET IO Device	No
• PROFINET CBA	Yes
• Open IE communication	Yes
• Media redundancy	No
<b>PROFINET IO Controller</b>	
• Transmission rate, max.	100 Mbit/s
<b>Services</b>	
— PG/OP communication	Yes
— S7 communication	Yes
— Isochronous mode	No
— IRT	No
— Prioritized startup	Yes
— Number of IO devices with prioritized startup.	32

max.	
— Number of connectable IO Devices, max.	128
— Number of connectable IO Devices for RT, max.	128
— of which in line, max.	128
— Activation/deactivation of IO Devices	Yes
— Number of IO Devices that can be simultaneously activated/deactivated, max.	8
— IO Devices changing during operation (partner ports), supported	Yes
— Device replacement without swap medium	Yes
— Send cycles	1 ms
— Updating time	1 to 512 ms (minimum value depends on communication share set for PROFINET I/O, on the number of I/O devices, and on the volume of configured user data)
<b>Address area</b>	
— Inputs, max.	16 kbyte
— Outputs, max.	16 kbyte
— User data per address area, max.	2 kbyte
— User data consistency, max.	254 byte
<b>PROFINET CBA</b>	
• acyclic transmission	Yes
• cyclic transmission	Yes
<b>Open IE communication</b>	
• Number of connections, max.	32
• Local port numbers used at the system end	0, 20, 21, 23, 25, 80, 102, 135, 161, 8080, 34962, 34963, 34964, 65532, 65533, 65534, 65535
• Keep-alive function, supported	Yes
<b>SIMATIC communication</b>	
• Number of connections, max.	16
<b>4. Interface</b>	
Interface type	PROFINET
Isolated	Yes
Number of simultaneously operable CPs, max.	1; CP 1616 (HW release 8 or above), CP 1604 (HW release 7 or higher), integrated PROFINET interface of SIMATIC PC and S7-mEC
automatic detection of transmission rate	Yes; 10/100 Mbit/s
Autonegotiation	Yes
Autocrossing	Yes
Change of IP address at runtime, supported	Yes
<b>Interface types</b>	
• Number of ports	3
• integrated switch	Yes
<b>Protocols</b>	
• PROFINET IO Controller	Yes
• PROFINET IO Device	No
• PROFINET CBA	Yes
• Open IE communication	Yes
• Web server	Yes
• Media redundancy	Yes
<b>PROFINET IO Controller</b>	
• Transmission rate, max.	100 Mbit/s
<b>Services</b>	
— PG/OP communication	Yes
— S7 communication	Yes
— Isochronous mode	Yes
— IRT	Yes
— Number of IO devices with prioritized startup, max.	32
— Number of connectable IO Devices, max.	256
— Of which IO devices with IRT, max.	64
— of which in line, max.	64
— Number of IO Devices with IRT and the option	64

"high flexibility"	
— of which in line, max.	32
— Number of connectable IO Devices for RT, max.	256
— of which in line, max.	256
— Activation/deactivation of IO Devices	Yes
— Number of IO Devices that can be simultaneously activated/deactivated, max.	8
— IO Devices changing during operation (partner ports), supported	Yes
— Device replacement without swap medium	Yes
— Send cycles	250 µs, 500 µs, 1 ms
— Updating time	0.25...512 depending on the send cycle
<b>Address area</b>	
— Inputs, max.	16 kbyte
— Outputs, max.	16 kbyte
— User data per address area, max.	2 kbyte
— User data consistency, max.	254 byte
<b>Open IE communication</b>	
• Local port numbers used at the system end	0, 20, 21, 25, 80, 102, 135, 161, 34962, 34963, 34964, 65532, 65533, 65534, 65535
<b>SIMATIC communication</b>	
• Number of connections, max.	32
<b>Protocols</b>	
<b>Open IE communication</b>	
• ISO-on-TCP (RFC1006)	Yes
— Number of connections, max.	32
— Data length, max.	65 534 byte
• UDP	Yes
— Number of connections, max.	32
— Data length, max.	1 472 byte
<b>Web server</b>	
• supported	Yes
• User-defined websites	No
• Number of HTTP clients	2
<b>Isochronous mode</b>	
Equidistance	Yes
Number of DP masters with isochronous mode	2
User data per isochronous slave, max.	128 byte
shortest clock pulse	2.2 ms; 2.2 ms without partial process image; 2.2 ms with partial process image
<b>Communication functions</b>	
PG/OP communication	Yes
Data record routing	Yes; only with CP 5611 or integrated PROFIBUS interface of the SIMATIC PC
<b>Global data communication</b>	
• supported	No
<b>S7 basic communication</b>	
• supported	No
<b>S7 communication</b>	
• supported	Yes
• as server	Yes
• as client	Yes
• User data per job, max.	64 kbyte; Depends on which block is used: BSEND/USEND or PUT/GET
<b>PROFINET CBA (at set setpoint communication load)</b>	
• Setpoint for the CPU communication load	20 %
• Number of remote interconnection partners	64
• Number of functions, master/slave	30
• Total of all master/slave connections	1 000
• Data length of all incoming connections master/slave, max.	6 800 byte

<ul style="list-style-type: none"> <li>• Data length of all outgoing connections master/slave, max.</li> </ul>	6 800 byte
<ul style="list-style-type: none"> <li>• Number of device-internal and PROFIBUS interconnections</li> </ul>	500
<ul style="list-style-type: none"> <li>• Data length of device-internal und PROFIBUS interconnections, max.</li> </ul>	4 000 byte
<ul style="list-style-type: none"> <li>• Data length per connection, max.</li> </ul>	1 400 byte
<b>Remote interconnections with acyclic transmission</b>	
— Sampling interval, min.	500 ms
— Number of incoming interconnections	100
— Number of outgoing interconnections	100
— Data length of all incoming interconnections, max.	2 000 byte
— Data length of all outgoing interconnections, max.	2 000 byte
— Data length per connection, max.	1 400 byte
<b>Remote interconnections with cyclic transmission</b>	
— Transmission frequency: Transmission interval, min.	10 ms
— Number of incoming interconnections	200
— Number of outgoing interconnections	200
— Data length of all incoming interconnections, max.	4 800 byte
— Data length of all outgoing interconnections, max.	4 800 byte
— Data length per connection, max.	250 byte
<b>HMI variables via PROFINET (acyclic)</b>	
— Number of stations that can log on for HMI variables (PN OPC/iMap)	3
— HMI variable updating	500 ms
— Number of HMI variables	200
— Data length of all HMI variables, max.	2 000 byte
<b>PROFIBUS proxy functionality</b>	
— supported	Yes
— Number of linked PROFIBUS devices	16
— Data length per connection, max.	240 byte; Slave-dependent
<b>Number of connections</b>	
<ul style="list-style-type: none"> <li>• overall</li> </ul>	96
<ul style="list-style-type: none"> <li>• usable for PG communication <ul style="list-style-type: none"> <li>— reserved for PG communication</li> </ul> </li> </ul>	1
<ul style="list-style-type: none"> <li>• usable for OP communication <ul style="list-style-type: none"> <li>— reserved for OP communication</li> </ul> </li> </ul>	1
<b>S7 message functions</b>	
Number of login stations for message functions, max.	62
SCAN procedure	No
simultaneously active Alarm-S blocks, max.	20; of a total of 20 for all SFCs
Alarm 8-blocks	Yes
<ul style="list-style-type: none"> <li>• Number of instances for alarm 8 and S7 communication blocks, max.</li> </ul>	4 000
Process control messages	No
<b>Test commissioning functions</b>	
Status block	Yes
Single step	Yes
Number of breakpoints	20
<b>Status/control</b>	
<ul style="list-style-type: none"> <li>• Status/control variable</li> </ul>	Yes
<b>Forcing</b>	
<ul style="list-style-type: none"> <li>• Forcing</li> </ul>	No
<b>Diagnostic buffer</b>	
<ul style="list-style-type: none"> <li>• present</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Number of entries, max. <ul style="list-style-type: none"> <li>— adjustable</li> </ul> </li> </ul>	Yes

— preset	120
<b>Hardware requirement</b>	
Hardware required	PC with color monitor, keyboard, mouse or pointing device for Windows
<b>Processor</b>	
• Processor	Intel Celeron M 900 MHz or compatible (older PC systems with Programmable Interrupt Controllers (PIC) are not suitable for WinAC RTX F 2010.)
— Multi-processor system	No
— Hyper-threading	Yes
<b>Memory</b>	
• Main memory, min.	1 Gbyte
• Required memory on hard disk	100 Mbyte
<b>Operating systems</b>	
pre-installed operating system	
• Windows XP Embedded	Yes; With the delivery image of the SIMATIC PC
— supported HAL types under Windows XP	ACPI uniprocessor PC, ACPI multiprocessor PC, MPS multiprocessor PC
• Windows Embedded Standard 7	No
<b>Configuration</b>	
Configuration software	
• STEP 7	Yes; As of V5.5 + HW update/S7 F Configuration Pack V5.5 + SP6 + HF1/option package S7 Distributed Safety V5.4 + SP5 or later
<b>Programming</b>	
• Nesting levels	8
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes
Software libraries	
— Easy Motion Control	Yes
— Software redundancy	Yes; As of V1.2, only for operation of WinAC RTX (F) with WinAC RTX (F)
Number of simultaneously active SFCs	
— DPSYC_FR	20; of a total of 20 for all SFCs
— D_ACT_DP	20; of a total of 20 for all SFCs
— RD_REC	20; of a total of 20 for all SFCs
— WR_REC	20; of a total of 20 for all SFCs
— WR_PARM	20; of a total of 20 for all SFCs
— PARM_MOD	20; of a total of 20 for all SFCs
— WR_DPARM	20; of a total of 20 for all SFCs
— DPNRM_DG	20; of a total of 20 for all SFCs
— RDSYSST	20; of a total of 20 for all SFCs
Number of simultaneously active SFBs	
— RDREC	20; of a total of 20 for all SFBs
— WRREC	20; of a total of 20 for all SFBs
<b>Know-how protection</b>	
• User program protection/password protection	Yes
<b>Open Development interfaces</b>	
• CCX (Custom Code Extension)	Yes; WinAC ODK V4.2 or higher
• CMI (Controller Management Interface)	Yes; WinAC ODK V4.2 or higher
• SMX (Shared Memory Extension)	Yes; WinAC ODK V4.2 or higher
— Inputs	4 kbyte
— Outputs	4 kbyte
<b>Weights</b>	
Weight, approx.	100 g; With packaging
<b>Further information</b>	

**Notes on Microsoft Updates 2018-01 (Meltdown and Spectre) with SIMATIC WinAC RTX**



<https://support.industry.siemens.com/cs/ww/en/view/109755177>

