



encoder interface card with RS422 compatible differential outpts - 5 V DC

VW3A3401

Main

Range of product	Altivar
Product or component type	Encoder interface card
Range compatibility	Altivar Lift Altivar 61 Altivar 71Q Altivar 71 Altivar 61Q
Discrete output type	Differential
Communication port protocol	RS422
[Us] rated supply voltage	5 V DC (voltage limits: 55.5 V)
Number of pulses per revolution	10000 for ATV71H383 5000 for all ATV61 drives 5000 for ATV71HM3 5000 for ATV71HM3X 5000 for ATV71HN4

Complementary

Maximum supply current	0.2 A
Protection type	Short-circuit protection Overload protection
Maximum cable distance between devices	50 m
Maximum operating frequency	300 kHz
Input signal	A B Compliment of A Compliment of B
Input impedance	440 Ohm
Electrical connection	Terminal, connection capacity: 0.2 mm² (AWG 24) <25 m cable length, encoder, 100 mA at 4.5 V Terminal, connection capacity: 0.5 mm² (AWG 20) <25 m cable length, encoder, 200 mA at 4.5 V Terminal, connection capacity: 0.5 mm² (AWG 20) <50 m cable length, encoder, 100 mA at 4.5 V Terminal, connection capacity: 0.75 mm² (AWG 18) <50 m cable length, encoder, 200 mA at 4.5 V
Net weight	0.2 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	147 g

Package 1 Height	7.5 cm
Package 1 width	17 cm
Package 1 Length	23 cm
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Weight	1.528 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months
----------	-----------