



# Ethernet module M580 - 3-port Ethernet communication

Local distributor code: 402706834 BMENOC0301

EAN Code: 3606480713903

## Main

Range of product	Modicon M580
Product or component type	Communication module
Product compatibility	BMEXBP Ethernet + X-bus rack
Concept	Transparent Ready

### Complementary

Complementary			
Integrated connection type	3 Ethernet, connector type: RJ45, transmission rate: 10/100 Mbit/s, transmission mode: double shielded twisted pair		
Web server	Basic		
Transmission support medium	Ethernet backplane		
Communication service	Bandwidth management FDR server SNMP network administrator Modbus TCP I/O Scanner and Messaging Ethernet/IP I/O Scanner and Messaging RSTP support Port mirroring Embedded multiport switch		
Port Ethernet	10BASE-T/100BASE-TX		
Supply	Internal power supply via rack		
Marking	CE		
Module format	Standard		
Current consumption	900 mA at 3.3 V DC (for product version >= 13) 1800 mA at 3.3 V DC (for product version < 13)		
Net weight	0.2 kg		

## **Environment**

Ambient air temperature for operation	060 °C
IP degree of protection	IP20
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility
Local signalling	1 LED (green) for processor running (RUN) 1 LED (red) for processor or system fault (ERR) 1 LED (green/red) for ETH MS (Ethernet port configuration status) 1 LED (green/red) for Eth NS (Ethernet network status)

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 cm
Package 1 Width	11.200 cm
Package 1 Length	12.000 cm
Package 1 Weight	254.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.136 kg

## Offer Sustainability

Sustainable offer status	Green Premium product		
REACh Regulation	REACh Declaration		
REACh free of SVHC	Yes		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration		
Mercury free	Yes		
China RoHS Regulation	China RoHS declaration		
RoHS exemption information	Yes		
Environmental Disclosure	Product Environmental Profile		
Circularity Profile	End of Life Information		
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins		

# **Contractual warranty**

Warranty 18 months


## **Product datasheet**

## BMENOC0301

**Dimensions Drawings** 

#### **Modules Mounted on Racks**

#### **Dimensions**



- (1) With removable terminal block (cage, screw or spring).
- (2) With FCN connector.
- (3) On AM1 ED rail: 35 mm wide, 15 mm deep. Only possible with BMXXBP0400/0400H/0600/0600H/0800/0800H rack.

Rack references	a in mm	a in in.
BMXXBP0400 and BMXXBP0400H	242.4	09.54
BMXXBP0600 and BMXXBP0600H	307.6	12.11
BMXXBP0800 and BMXXBP0800H	372.8	14.68
BMXXBP1200 and BMXXBP1200H	503.2	19.81

#### Recommended replacement(s)